(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date7 October 2004 (07.10.2004)

PCT

$\begin{array}{c} \hbox{\scriptsize (10) International Publication Number} \\ \hbox{\scriptsize WO 2004/086809} \ \ A2 \end{array}$

(51) International Patent Classification7:

H04R

(21) International Application Number:

PCT/US2004/008620

- (22) International Filing Date: 22 March 2004 (22.03.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10/394,499

20 March 2003 (20.03.2003) US


- (71) Applicant (for all designated States except US): OTO-LOGICS LLC [US/US]; 5445 Airport Boulevard, Boulder, Colorado 80301 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): EASTER, James, Roy [US/US]; 286 Wichita Road, Lyons, Colorado 80540

(US). KASIC, James, Frank, II [US/US]; 4785 Harrison Avenue, Boulder, Colorado 80303 (US). BEDOYA, Jose, H. [US/US]; 604 10th Street, Boulder, Colorado 80302 (US). SCHNEIDER, Robert, Edwin [US/US]; 2777 Hughs Drive, Erie, Colorado 80516 (US).

- (74) Agent: MARSH, Thomas, R.; MARSH FISCHMANN & BREYFOGLE LLP, 3151 South Vaughn Way, Suite 411, Aurora, Colorado 80014 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: IMPROVED APPARATUS AND METHOD FOR OSSICULAR FIXATION OF IMPLANTABLE HEARING AID ACTUATOR



(57) Abstract: The invention is directed to a fixation apparatus and method for interfacing an implantable hearing aid actuator with the ossicular chain of a patient. The fixation apparatus may include one or more surface discontinuities to enhance tissue fixation and thereby yield enhanced mechanical coupling and vibratory response. Surface discontinuities may be in the form of surface pores, surface asperities and complex surface shapes such as grooves, slots, lips or openings formed in the fixation apparatus. The fixation apparatus may also and/or alternatively include a portion or component that is deflectable or that comprises a conditioned shape memory material that is activatable at bodily temperatures to yield a degree of lateral loading when the fixation apparatus is positioned within an opening defined within a bone of the ossicular chain of a patient, thereby yielding enhanced mechanical coupling.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.